
Disclaimer. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Ethernet ConneXium cable - shielded twisted pair crossed cord - 15 m - 2 x RJ45

490NTC00015

! Discontinued on: 30 Jun 2023



Main

Range Of Product	Modicon Premium Automation platform
Bus Type	Ethernet
Accessory / Separate Part Category	Connection accessories
Accessory / Separate Part Type	Connecting cable
Accessory / Separate Part Designation	Shielded twisted pair crossed cord cable
Accessory / Separate Part Destination	Connection between hub, switch and transceiver
Cable Length	15 m

Complementary

Electrical Connection	2 connectors
Connector Type	RJ45

Environment

Standards	EIA-568 category 5 EN 50173 class D	
	IEC 11801 class D TIA-568 category 5	

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	4.5 cm
Package 1 Width	26.5 cm
Package 1 Length	28 cm
Package 1 Weight	790 g
Unit Type Of Package 2	S04
Number Of Units In Package 2	5
Package 2 Height	30 cm
Package 2 Width	40 cm
Package 2 Length	60 cm
Package 2 Weight	4.6 kg

Contractual warranty

Warranty

18 months

16 May 2024

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Well-being performance

V Toxic Heavy Metal Free	
Mercury Free	
Rohs Exemption Information	Yes
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	Chica Dall's deglaration
China None Negaration	China RoHS declaration