# **Product datasheet**

Specifications





# iQuick PRD40r modular surge arrester - 3 poles + N - 350V - with remote transfer

A9L16294

### Main

| Range Of Product            | Acti9                                   |
|-----------------------------|---|
| Product Name                | Acti9 iQuick PRD                        |
| Product Or Component Type   | Surge arrester with pluggable cartridge |
| Device Short Name           | iQuick PRD40r                           |
| Device Application          | Distribution                            |
| Standards                   | EN 61643-11:2012<br>IEC 61643-11:2011   |
| Product Certifications      | CE                                      |
| Quality Labels              | KEMA-KEUR<br>NF                         |
| Poles Description           | 3P + N                                  |
| Remote Signalling           | With                                    |
| Signal Contacts Composition | 1 SD (1 C/O)                            |
| Surge Arrester Type         | Electrical distribution network         |
| Earthing System             | TN-S<br>TT                              |

## Complementary

| Surge Arrester Class Type                    | Type 2   |
|--|--|
| Surge Arrester Technology                    | MOV + GDT  |
| [Ue] Rated Operational Voltage               | 230/400 V AC (+/- 10 %) at 50/60 Hz  |
| [In] Nominal Discharge Current               | Common mode: 20 kA (L/PE)<br>Common mode: 20 kA (N/PE)<br>Differential mode: 20 kA (L/N)                   |
| [Imax] Maximum Discharge<br>Current          | Common mode: 40 kA L/PE<br>Common mode: 40 kA N/PE<br>Differential mode: 40 kA L/N                         |
| [Uc] Maximum Continuous<br>Operating Voltage | Common mode: 264 V N/PE<br>Common mode: 350 V L/PE<br>Differential mode: 350 V L/N                         |
| Maximum [Up] Voltage Protection<br>Level     | Common mode <1.5 kV type 2 L/PE<br>Common mode <1.5 kV type 2 N/PE<br>Differential mode <2.5 kV type 2 L/N |
| Disconnector Device Type                     | Integrated circuit breaker - Icu 20 kA   |
| Signalling Circuit Voltage                   | 2 A/250 V AC 50/60 Hz  |
| Mounting Mode                                | Clip-on (DIN rail)   |
| 9 Mm Pitches                                 | 14.7   |

| Height                  | 94 mm  |  |
|-------------------------|--|--|
| Width                   | 131.5 mm   |  |
| Depth                   | 75.9 mm  |  |
| Net Weight              | 0.86 kg  |  |
| Colour                  | White (RAL 9003)   |  |
| Connections - Terminals | Tunnel type terminal (upside) 2.535 mm <sup>2</sup><br>Tunnel type terminal (downside) 2.525 mm <sup>2</sup> |  |
| Tightening Torque       | 2.5 N.m  |  |

### Environment

| Ik Degree Of Protection                  | IK05 conforming to IEC 62262 |
|--|------------------------------|
| Relative Humidity                        | 595 %                        |
| Operating Altitude                       | 2000 m                       |
| Ambient Air Temperature For<br>Operation | -2560 °C                     |
| Ambient Air Temperature For<br>Storage   | -4070 °C                     |

# **Packing Units**

| -                            |           |
|------------------------------|-----------|
| Unit Type Of Package 1       | PCE       |
| Number Of Units In Package 1 | 1         |
| Package 1 Height             | 9.500 cm  |
| Package 1 Width              | 11.000 cm |
| Package 1 Length             | 15.500 cm |
| Package 1 Weight             | 891.000 g |
| Unit Type Of Package 2       | S03       |
| Number Of Units In Package 2 | 12        |
| Package 2 Height             | 30.000 cm |
| Package 2 Width              | 30.000 cm |
| Package 2 Length             | 40.000 cm |
| Package 2 Weight             | 11.180 kg |
|                              |           |

### **Contractual warranty**

Warranty

18 months

# Sustainability Screen Premium

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

#### Well-being performance

Mercury Free
Rohs Exemption Information
Yes
Halogen Free Plastic Parts & Cables

### **Certifications & Standards**

Product

| Reach Regulation         | REACh Declaration   |
|--------------------------|---|
| Eu Rohs Directive        | Compliant with Exemptions   |
| China Rohs Regulation    | China RoHS declaration<br>Product out of China RoHS scope. Substance declaration for your information                       |
| Environmental Disclosure | Product Environmental Profile   |
| Weee                     | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Circularity Profile      | No need of specific recycling operations  |