Product datasheet

Specifications





Thermistor probe, TeSys LT3, surface probe, 80°C, 0 to 2.5V, bulk qty

DA1TS080

Main

Range Of Product	DA1
Product Or Component Type	Thermistor probe
Device Short Name	DA1TS
Accessory / Separate Part Category	Protection accessory
Quantity Per Set	Set of 10
Ambient Air Temperature For Operation	80 °C

Complementary

[Ui] Rated Insulation Voltage	1000 V
[Ue] Rated Operational Voltage	<= 2.5 V
Resistance	250 Ohm per probe 25 °C
Insulation	Reinforced
Cable Length	1 m between probe and motor terminal plate
Net Weight	0.005 kg

Environment

Standards

IEC 60034-11 Mark A

Packing Units

U	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	2.0 cm
Package 1 Width	10.0 cm
Package 1 Length	15.0 cm
Package 1 Weight	8.0 g
Unit Type Of Package 2	BAG
Number Of Units In Package 2	10
Package 2 Height	15.0 cm
Package 2 Width	10.0 cm
Package 2 Length	2.0 cm
Package 2 Weight	89.0 g
Unit Type Of Package 3	S01

Number Of Units In Package 3	100
Package 3 Height	15.0 cm
Package 3 Width	15.0 cm
Package 3 Length	40.0 cm
Package 3 Weight	1.137 kg

Contractual warranty

Warranty

18 months

Sustainability Screen

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Yes

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Mercury Free

Rohs Exemption Information

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information