



Cam switch body, Harmony K, Ø 22mm, plastic, 3 pole, with 0 position, 45°, 20A

K2C003A

Main

Range Of Product	Harmony K	
Product Or Component Type	Cam switch body	
Component Name	K2	
[Ith] Conventional Free Air Thermal Current	20 A	
Sub-Assembly Composition	Contact blocks + fixing plate	
Cam Switch Function	Switch	
Off Position	With Off position	
Poles Description	3P	
Switching Positions	Right: 0° - 45°	
Mounting Location	Front	
Fixing Mode	Ø 22 mm hole	
Bezel Material	Plastic	

Complementary

Switching Angle	45 °	
[Ui] Rated Insulation Voltage	690 V (pollution degree 3) conforming to IEC 60947-1	
[Ithe] Conventional Enclosed Thermal Current	16 A	
Rated Operational Power In W	1300 W AC-3, 230 V 1 phase conforming to IEC 947-3	
	14000 W AC-21, 400 V 3 phases conforming to IEC 947-3	
	17000 W AC-21, 500 - 660 V 3 phases conforming to IEC 947-3	
	2200 W AC-3, 230 V 3 phases conforming to IEC 947-3	
	2200 W AC-3, 400 V 1 phase conforming to IEC 947-3	
	4000 W AC-23A, 230 V 3 phases conforming to IEC 947-3	
	4000 W AC-3, 400 V 3 phases conforming to IEC 947-3	
	4000 W AC-3, 500 V 3 phases conforming to IEC 947-3	
	4000 W AC-3, 690 V 3 phases conforming to IEC 947-3	
	5500 W AC-23A, 400 V 3 phases conforming to IEC 947-3	
	5500 W AC-23A, 500 V 3 phases conforming to IEC 947-3	
	5500 W AC-23A, 690 V 3 phases conforming to IEC 947-3	
	8000 W AC-21, 230 V 3 phases conforming to IEC 947-3	

[le] Rated Operational Current Ac 8 A at 400 V AC-3 3 phases conforming to IEC 947-3

10.8 A at 400 V AC-23A 3 phases conforming to IEC 947-3
14.6 A at 230 V AC-23A 3 phases conforming to IEC 947-3
4.7 A at 690 V AC-3 3 phases conforming to IEC 947-3
6.4 A at 690 V AC-23A 3 phases conforming to IEC 947-3
6.5 A at 500 V AC-3 3 phases conforming to IEC 947-3
8.3 A at 230 V AC-3 3 phases conforming to IEC 947-3
8.9 A at 500 V AC-23A 3 phases conforming to IEC 947-3
2 A at 500 V AC-15 conforming to IEC 947-5-1
3 A at 400 V AC-15 conforming to IEC 947-5-1
4 A at 230 V AC-15 conforming to IEC 947-5-1

Electrical Durability	200000 cycles AC-23 200000 cycles AC-3 600000 cycles AC-15 600000 cycles AC-21	
Maximum Operating Rate	2.5 cyc/mn AC-21 2.5 cyc/mn AC-23 2.5 cyc/mn AC-3 8.333 cyc/mn AC-15	
Short-Circuit Current	10000 A	
Short-Circuit Protection	20 A cartridge fuse, type gG	
[Uimp] Rated Impulse Withstand Voltage	4 kV in isolating function 6 kV conforming to IEC 947-1	
Contact Operation	Slow-break	
Positive Opening	With	
Electrical Connection	Captive screw clamp terminals flexible, clamping capacity: 2 x 1.5 mm ² Captive screw clamp terminals solid, clamping capacity: 1 x 2.5 mm ²	
Mechanical Durability	urability 1000000 cycles	
Net Weight	0.105 kg	

Environment

Standards	IEC 60947-3 for power circuit IEC 60947-5-1 for control circuit CENELEC EN 50013	
Product Certifications	CSA 240 V 3 hp 3 phases 2 -pole(s) UL 240 V 0.33 hp 1 phase 2 -pole(s) CSA 240 V 1 hp 1 phase UL 240 V 1 hp 3 phases	
Protective Treatment	TC	
Ambient Air Temperature For Operation	-2555 °C	
Ambient Air Temperature For Storage	-4070 °C	
Shock Resistance	30 gn conforming to IEC 68-2-27	
Vibration Resistance	5 gn conforming to IEC 68-2-6 (f = 10150 Hz)	
Overvoltage Category	Class II conforming to IEC 536 Class II conforming to NF C 20-030	

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	6.5 cm
Package 1 Width	6.5 cm
Package 1 Length	8.0 cm
Package 1 Weight	116.0 g
Unit Type Of Package 2	S01
Number Of Units In Package 2	16
Package 2 Height	15.0 cm
Package 2 Width	15.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	2.081 kg

Contractual warranty

Warranty

18 months

Sustainability Green Premium

Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

⊘	Reach Free Of Svhc	
⊘	Toxic Heavy Metal Free	
⊘	Mercury Free	
⊘	Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations