# **Product datasheet**

Specifications





# Enclosed DOL starter, TeSys LE, 18A,220V AC coil, including 1 LC1D,2 pushbuttons

LE1D18M7

#### Main

| Range                     | TeSys   |
|---------------------------|---|
| Product Name              | TeSys LE  |
| Device Short Name         | LE1D  |
| Product Or Component Type | Enclosed DOL starter                                      |
| Device Application        | Standard  |
| Utilisation Category      | AC-3  |
| Device Composition        | Thermal overload relay ordered separately<br>Contactor    |
| Control Type              | Push-button start green I<br>Push-button stop/reset red O |

#### Complementary

| · · · · · · · · · · · · · · · · · ·            |  |
|--|--|
| Motor Power Kw                                 | 10 kW at 500 V AC 50/60 Hz<br>10 kW at 660/690 V AC 50/60 Hz<br>4 kW at 220/230 V AC 50/60 Hz<br>9 kW at 415 V AC 50/60 Hz<br>9 kW at 440 V AC 50/60 Hz<br>7.5 kW at 380/400 V AC 50/60 Hz |
| [Ith] Conventional Free Air<br>Thermal Current | 17 A   |
| [Uc] Control Circuit Voltage                   | 220 V AC 50/60 Hz  |
| Cable Entry Number                             | 2 ISO20 top<br>2 ISO25 top<br>2 ISO20 bottom<br>2 ISO25 bottom   |
| Width  | 101 mm   |
| Height   | 201 mm   |
| Depth  | 153.5 mm   |
| Net Weight                                     | 1.015 kg   |

## Environment

| Material                                 | Polycarbonate                |  |
|--|------------------------------|--|
| Ip Degree Of Protection                  | IP65 conforming to IEC 60529 |  |
| Ik Degree Of Protection                  | IK07 conforming to IEC 60529 |  |
| Standards                                | IEC 60947-4-1                |  |
| Ambient Air Temperature For<br>Operation | -540 °C                      |  |
| Environmental Characteristic             | Standard environment         |  |

| Product | Certifications |
|---------|----------------|
|---------|----------------|

## **Packing Units**

| Unit Type Of Package 1       | PCE       |
|------------------------------|-----------|
| Number Of Units In Package 1 | 1         |
| Package 1 Height             | 19.500 cm |
| Package 1 Width              | 16.000 cm |
| Package 1 Length             | 24.800 cm |
| Package 1 Weight             | 1.186 kg  |
| Unit Type Of Package 2       | P06       |
| Number Of Units In Package 2 | 22        |
| Package 2 Height             | 75.000 cm |
| Package 2 Width              | 60.000 cm |
| Package 2 Length             | 80.000 cm |
| Package 2 Weight             | 38.630 kg |
|                              |           |

# **Contractual warranty**

Warranty

18 months

## Sustainability Screen Premium

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

#### Well-being performance

Reach Free Of Svhc
Toxic Heavy Metal Free
Mercury Free
Rohs Exemption Information Yes

#### **Certifications & Standards**

| Reach Regulation         | REACh Declaration  |
|--------------------------|--|
| Eu Rohs Directive        | Compliant<br>EU RoHS Declaration   |
| China Rohs Regulation    | China RoHS declaration   |
| Environmental Disclosure | Product Environmental Profile  |
| Weee                     | The product must be disposed on European Union markets following specific waste<br>collection and never end up in rubbish bins |
| Circularity Profile      | End of Life Information  |