# **Product datasheet**

Specifications





# Advanced control unit, TeSys Ultra, 3P, 0.35 to 1.05A, protection & diagnostic, class 20, 24VDC coil

LUCDT1BL

() Discontinued on: 2 Jan 2024

(!) Discontinued

#### Main

Mann		
Range	TeSys	
Range Of Product	TeSys Ultra	
Device Short Name	LUCD	
Product Or Component Type	Advanced control unit	
Device Application	Motor control Motor protection	
Product Specific Application	Basic protection and advanced functions, communication	
Main Function Available	Protection against phase failure and phase imbalance Manual reset Protection against overload and short-circuit Earth fault protection	
Product Compatibility	Power base LUTM	
Network Frequency	4060 Hz	
Load Type	3-phase motor - cooling: self-cooled	
Utilisation Category	AC-41 AC-44 AC-43	
Rated Motor Current Adjustment Range	0.351.05 A	
Thermal Overload Class	Class 20 - frequency limit: 4060 Hz - temperature compensation: -2570 °C conforming to IEC 60947-6-2 Class 20 - frequency limit: 4060 Hz - temperature compensation: -2570 °C conforming to UL 508	
Tripping Threshold	14.2 x lr +/- 20 %	
Phase Failure Sensitivity	Yes	
[Uc] Control Circuit Voltage	24 V DC	

### Complementary

Control Circuit Voltage Limits	2028 V for DC circuit 24 V in operation 14.5 V for DC circuit 24 V drop-out	
Typical Current Consumption	130 mA at 24 V DC I maximum while closing 60 mA at 24 V DC I rms sealed	
Heat Dissipation	2 W for control circuit	
Operating Time	35 ms opening for control circuit 70 ms closing for control circuit	
Reset	Manual reset	

Standards	EN 60947-6-2 IEC 60947-6-2 UL 508 CSA C22.2 No 14	
Product Certifications	UL CSA	
[Ui] Rated Insulation Voltage	250 V conforming to IEC 60947-6-2 250 V conforming to UL 60947-4-1 250 V conforming to CSA C22.2 No 60947-4-1	
[Uimp] Rated Impulse Withstand Voltage	4 kV conforming to IEC 60947-6-2	
Fixing Mode	Plug-in (front face)	
Width	45 mm	
Height	66 mm	
Depth	60 mm	
Compatibility Code	LUCD	

### Environment

Ip Degree Of Protection	IP20 front panel and wired terminals conforming to IEC 60947-1 IP20 other faces conforming to IEC 60947-1	
	IP40 front panel outside connection zone conforming to IEC 60947-1	
Protective Treatment	TH conforming to IEC 60068	
Ambient Air Temperature For Operation	-2570 °C	
Ambient Air Temperature For Storage	-4085 °C	
Operating Altitude	2000 m	
Fire Resistance	960 °C parts supporting live components conforming to IEC 60695-2-12 650 °C conforming to IEC 60695-2-12	
Shock Resistance	10 gn power poles open conforming to IEC 60068-2-27 15 gn power poles closed conforming to IEC 60068-2-27	
Vibration Resistance	2 gn, 5300 Hz, power poles open conforming to IEC 60068-2-6 4 gn, 5300 Hz, power poles closed conforming to IEC 60068-2-6	
Resistance To Electrostatic Discharge	8 kV level 3 in open air conforming to IEC 61000-4-2 8 kV level 4 on contact conforming to IEC 61000-4-2	
Non-Dissipating Shock Wave	1 kV serial mode conforming to IEC 60947-6-2 2 kV common mode conforming to IEC 60947-6-2	
Resistance To Radiated Fields	10 V/m 3 conforming to IEC 61000-4-3	
Resistance To Fast Transients	2 kV class 3 serial link conforming to IEC 61000-4-4 4 kV class 4 all circuits except for serial link conforming to IEC 61000-4-4	
Immunity To Radioelectric Fields	10 V conforming to IEC 61000-4-6	
Immunity To Microbreaks	3 ms	
Immunity To Voltage Dips	70 % / 500 ms conforming to IEC 61000-4-11	

# **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	5.4 cm
Package 1 Width	8.0 cm
Package 1 Length	10.0 cm
Package 1 Weight	134.0 g

2

Unit Type Of Package 2	S02
Number Of Units In Package 2	23
Package 2 Height	15.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	3.43 kg

### **Contractual warranty**

Warranty

18 months

## Sustainability Screen Premium

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

#### Well-being performance

Mercury Free
Rohs Exemption Information Yes
Pvc Free

Halogen Free Plastic Parts Product

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information