Product datasheet

Specification





Miniature circuit breaker (MCB), Multi9 C60H-DC, 2P, 6A, C curve, 5kA (UL1077), 6kA (IEC/EN 60947-2)

M9U21206

Main

Mani		
ange Multi9		
Product Name	Multi9 C60H-DC	
Product Or Component Type	Miniature circuit-breaker	
Device Short Name	C60H-DC	
Device Application Distribution		
Poles Description	2P	
Number Of Protected Poles	2	
[In] Rated Current 6 A at 25 °C conforming to EN/IEC 60947-2		
Network Type DC		
Trip Unit Technology	Thermal-magnetic	
Curve Code	С	
Breaking Capacity	20 kA Icu at 220 V DC conforming to EN/IEC 60947-2 10 kA Icu at 440 V DC conforming to EN/IEC 60947-2 6 kA Icu at 500 V DC conforming to EN/IEC 60947-2 5 kA AIR at 12500 V DC conforming to UL 1077 20 kA Icu at 220 V DC conforming to GB 14048.2 10 kA Icu at 440 V DC conforming to GB 14048.2 6 kA Icu at 500 V DC conforming to GB 14048.2	
Utilisation Category Category A conforming to EN/IEC 60947-2		
Suitability For Isolation	Yes conforming to EN/IEC 60947-2	
Standards	GB 14048.2 UL 1077	
Product Certifications	IEC CCC UR	

Complementary

[Ue] Rated Operational Voltage	220 V DC 440 V DC 500 V DC	
Magnetic Tripping Limit	710 x ln DC	
[Ics] Rated Service Breaking Capacity	7.5 kA 75 % conforming to EN/IEC 60947-2 - 440 V DC 4.5 kA 75 % conforming to EN/IEC 60947-2 - 500 V DC 15 kA 75 % conforming to EN/IEC 60947-2 - 220 V DC 7.5 kA 75 % conforming to GB 14048.2 - 440 V DC 4.5 kA 75 % conforming to GB 14048.2 - 500 V DC 15 kA 75 % conforming to GB 14048.2 - 220 V DC	
[Ui] Rated Insulation Voltage	500 V DC conforming to EN/IEC 60947-2	

14 May 2024 Life Is On Schneider

-		
[Uimp] Rated Impulse Withstand Voltage	d 6 kV conforming to EN/IEC 60947-2	
Contact Position Indicator	Yes	
Control Type	Toggle	
Local Signalling	ON/OFF indication	
Mounting Mode	Clip-on	
Mounting Support	DIN rail	
9 Mm Pitches	4	
Height	81 mm	
Width	36 mm	
Depth	73 mm	
Net Weight	0.128 kg	
Colour	Grey	
Mechanical Durability	20000 cycles	
Electrical Durability	3000 cycles 250 V DC L/R = 2 ms 6000 cycles 250 V DC	
Provision For Padlocking	Padlockable	
Connections - Terminals	Tunnel type terminal (top or bottom)125 mm² (AWG 18AWG 4) - rigid stranded Tunnel type terminal (top or bottom)116 mm² (AWG 18AWG 6) - flexible Tunnel type terminal (top or bottom)116 mm² (AWG 18AWG 6) - flexible with ferrule Tunnel type terminal (top or bottom) - 2 cable(s) 110 mm² (AWG 18AWG 8) - rigid stranded Tunnel type terminal (top or bottom) - 2 cable(s) 110 mm² (AWG 18AWG 8) - flexible Tunnel type terminal (top or bottom) - 2 cable(s) 110 mm² (AWG 18AWG 8) - flexible with ferrule Tunnel type terminal (top or bottom) - 3 cable(s) 1 mm² (AWG 18) - flexible stranded	
Wire Stripping Length	14 mm for top or bottom connection	
Tightening Torque	2.5 N.m top or bottom	
Earth-Leakage Protection	Without	

Environment

Heat Dissipation	5.4 W at 440 V - 6 A
Ip Degree Of Protection	IP20 conforming to IEC 60529 IP40 (modular enclosure) conforming to IEC 60529
Pollution Degree	3 conforming to EN/IEC 60947-2
Tropicalisation	2 conforming to IEC 60068-2 2 conforming to GB 14048.2
Relative Humidity	95 % at 55 °C
Ambient Air Temperature For Operation	-2570 °C
Ambient Air Temperature For Storage	-4085 °C

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	8.5 cm
Package 1 Width	3.6 cm

Package 1 Length	7.5 cm
Package 1 Weight	223.0 g
Unit Type Of Package 2	BB1
Number Of Units In Package 2	6
Package 2 Height	9.0 cm
Package 2 Width	8.0 cm
Package 2 Length	23.0 cm
Package 2 Weight	1.387 kg
Unit Type Of Package 3	S03
Number Of Units In Package 3	72
Package 3 Height	30.0 cm
Package 3 Width	30.0 cm
Package 3 Length	40.0 cm
Package 3 Weight	17.131 kg



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

⊘	Reach Free Of Svhc	
⊘	Toxic Heavy Metal Free	
Ø	Mercury Free	
⊘	Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations