



# reversible internal door polyester 2 locks grid pattern forPLM43

NSYPAP43G

### Main

Range	Thalassa
Accessory / Separate Part Category	Enclosure accessory
Product Or Component Type	Door
Application	Multi-purpose
For Enclosure Nominal Dimensions	-
Mounting Location	Front side
Range Compatibility	Thalassa Thalassa PLM
Device Composition	1 door 1 handle 4 fixing brackets

## Complementary

Material	Polyester charged with fibreglass	
Colour	Grey (RAL 7035)	
Lock Type	Lock 5 mm double bar	
Number Of Locks	2	
Door Type	Internal plain	
Door Opening Side	Reversible (110 °)	
Height	Grid pattern: 315 mm	
Width	Grid pattern: 205 mm	
Depth	Available depth between enclosure door : 26 mm Available depth between rear : 152 mm	

## **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	4.3 cm
Package 1 Width	27.5 cm
Package 1 Length	39.5 cm
Package 1 Weight	960.0 g
Unit Type Of Package 2	PAM
Number Of Units In Package 2	150
Package 2 Height	120 cm

Package 2 Width	100 cm
Package 2 Length	140 cm
Package 2 Weight	185 kg



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

#### Well-being performance



Mercury Free



Rohs Exemption Information

Yes

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations