Product datasheet

Specification





Isolated analog converter, Harmony Analog, 0…15A current to 0…10V or 4...20mA

RMCA61BD

Main

Range Of Product	Harmony Analog	
Product Or Component Type	Voltage/current converter	
Analogue Input Type	Current 01.5 A AC/DC 50/60 Hz Current 015 A AC/DC 50/60 Hz Current 05 A AC/DC 50/60 Hz	
Analogue Output Type	Current 020 mA <= 500 Ohm by cabling Current 420 mA <= 500 Ohm by cabling Voltage 010 V >= 100 kOhm by cabling	

Complementary

Protection Type	Reverse polarity protection on output Short-circuit protection on output Overvoltage protection on output (+/- 30 V)	
Abnormal Analogue Output Voltage	-150 V no input or input wire broken	
Abnormal Analogue Output Current	-300 mA, output selected 020 mA no input or input wire broken 430 mA, output selected 420 mA no input or input wire broken	
[Us] Rated Supply Voltage	24 V DC +/- 20 %, isolated	
Current Consumption	<= 70 mA for voltage output <= 90 mA for current output	
Local Signalling	LED (green) for power ON	
Measurement Error	+/- 5 % of full scale at 20 °C (temporary performance degradation when subject to electromagnetic interference)	
Repeat Accuracy	+/- 0.2 % full scale at 20 °C +/- 0.6 % full scale at 60 °C	
Temperature Coefficient	1000 ppm/°C, range: 05 A 2000 ppm/°C, range: 015 A 500 ppm/°C, range: 01.5 A	
Clamping Connection Capacity	2 x 1.5 mm ² 1 x 2.5 mm ²	
Tightening Torque	0.61.1 N.m	
Marking	CE	
Surge Withstand	0.5 kV during 1.2/50 µs conforming to IEC 61000-4-5	
[Ui] Rated Insulation Voltage	2 kV	
Fixing Mode	By screws (mounting plate) Clip-on (35 mm symmetrical DIN rail)	
Safety Reliability Data	B10d = 22108 MTTFd = 23.9 years	
Net Weight	0.15 kg	

Environment

Standards	IEC 60947-1
	IEC 60584-1
Product Certifications	CSA
	UL
	GL
Ip Degree Of Protection	IP20 (terminal block)
	IP50 (housing)
Fire Resistance	850 °C conforming to IEC 60695-2-1
	850 °C conforming to UL
Shock Resistance	50 gn for 11 ms conforming to IEC 60068-2-27
Vibration Resistance	5 gn (f= 10100 Hz) conforming to IEC 60068-2-6
Resistance To Electrostatic	6 kV (in contact) conforming to IEC 61000-4-2 level 3
Discharge	8 kV (in air) conforming to IEC 61000-4-2 level 3
Resistance To Fast Transients	1 kV (on input-output) conforming to IEC 61000-4-4
	2 kV (on power supply) conforming to IEC 61000-4-4
Disturbance Radiated/Conducted	CISPR 11
	CISPR 22 group 1 - class B
Ambient Air Temperature For Storage	-4085 °C
Ambient Air Temperature For Operation	050 °C mounting side by side
	060 °C 2 cm spacing
Pollution Degree	2 conforming to IEC 60664-1

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	4.852 cm
Package 1 Width	8.168 cm
Package 1 Length	8.397 cm
Package 1 Weight	160.0 g
Unit Type Of Package 2	S02
Number Of Units In Package 2	33
Package 2 Height	15 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	6.131 kg
Unit Type Of Package 3	P06
Number Of Units In Package 3	528
Package 3 Height	75 cm
Package 3 Width	60 cm
Package 3 Length	80 cm
Package 3 Weight	106 kg

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards


Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

RMCA61BD

Dimensions Drawings

Analog Interface: Voltage/Current Converter

Dimensions



(1) Terminal block AB1TP435U or AB1RRNTP435U2


Product datasheet

RMCA61BD


Mounting and Clearance

Mounting

Mounting on Rails AM1 *****



Panel Mounting




RMCA61BD

Connections and Schema

Analog Interface: Voltage/Current Converter

Wiring Diagram



- (1) Use 1 input only.
- (2) Use 1 output only.

The input, output and power supply lines must be kept away from the power cables to avoid effects due to induced interference.

The supply, input and output cables must be shielded as indicated in the schemes and must be kept away from each other.