Product datasheet

Specifications





smart communication module, Modicon M262, CANopen, 1 SubD9

TMSCO1

Main

Range Of Product	Modicon M262
Product Or Component Type	Smart communication module

Complementary

Range Compatibility	Modicon M262
Current Consumption	50 mA at 24 V
Number Of Module Per Pic	maximum per logic controller maximum per motion controller
Services	Maximum 63 slave nodes
Communication Port Protocol	CANopen
Local Signalling	1 LED (green) for PWR 1 LED (green/red) for MOD STS 1 LED (green) for CAN RUN 1 LED (red) for CAN ERR
Mounting Support	Top hat type TH35-15 rail conforming to IEC 60715 Top hat type TH35-7.5 rail conforming to IEC 60715 plate or panel with fixing kit
Width	30 mm
Height	100 mm
Depth	88.3 mm

Environment

Standards	UL 61010-1 UL 61010-2-201 CSA C22.2 No 61010-1 CSA C22.2 No 61010-2-201 CSA C22.2 No 213 ANSI/ISA 12-12-01 IEC 61131-2
Product Certifications	CE cULus RCM EAC (pending) Achilles
Resistance To Electrostatic Discharge	4 kV on contact conforming to IEC 61000-4-2 8 kV on air conforming to IEC 61000-4-2
Resistance To Electromagnetic Fields	10 V/m 80 MHz1 GHz conforming to IEC 61000-4-3 3 V/m 1.4 GHz2 GHz conforming to IEC 61000-4-3 1 V/m 2 GHz3 GHz conforming to IEC 61000-4-3

Resistance To Fast Transients	2 kV (power lines) conforming to IEC 61000-4-4
	1 kV (Ethernet line) conforming to IEC 61000-4-4
	1 kV (serial link) conforming to IEC 61000-4-4
	1 kV (input) conforming to IEC 61000-4-4
	1 kV (transistor output) conforming to IEC 61000-4-4
Resistance To Conducted	10 V 0.1580 MHz conforming to IEC 61000-4-4
Disturbances	3 V 0.180 MHz conforming to Marine specification (LR, ABS, DNV, GL)
	10 V spot frequency (2, 3, 4, 6.2, 8.2, 12.6, 16.5, 18.8, 22, 25 MHz) conforming to
	Marine specification (LR, ABS, DNV, GL)
Electromagnetic Emission	Conducted emissions - test level: 12069 dBµV/m QP (power lines) at 10150 kHz
	conforming to IEC 55011 Conducted emissions - test level: 63 dBμV/m QP (power lines) at 1.530 MHz
	conforming to IEC 55011
	Radiated emissions - test level: 40 dBμV/m A at 30230 kHz conforming to IEC 55011
	Conducted emissions - test level: 7963 dBµV/m QP (power lines) at 1501500
	kHz conforming to IEC 55011
	Radiated emissions - test level: 47 dBµV/m A at 2301000 MHz conforming to IEC
	55011
Ambient Air Temperature For	-2060 °C horizontal installation
Operation	-2050 °C vertical installation
Ambient Air Temperature For Storage	-4085 °C
Relative Humidity	1095 %, without condensation (in operation)
	1095 %, without condensation (in storage)
Ip Degree Of Protection	IP20
Pollution Degree	2
Operating Altitude	02000 m
Storage Altitude	03000 m
Vibration Resistance	3.5 mm at 28.4 Hz on symmetrical rail
	1 gn at 8.4200 Hz on symmetrical rail
	3.5 mm at 28.4 Hz on panel mounting
	1 gn at 8.4200 Hz on panel mounting
Shock Resistance	15 gn for 11 ms

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	6.3 cm
Package 1 Width	11.8 cm
Package 1 Length	16.9 cm
Package 1 Weight	250 g



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information

TMSCO1

Dimensions Drawings

Side and Front Views



