

Product datasheet

Specifications



serial link tap isolation box - for PLC Twido - screw terminal block - 2 RJ45

TWDXCAISO

Main

Range Of Product	Twido
Accessory / Separate Part Category	Connection accessories
Accessory / Separate Part Type	Tap isolation box
Accessory / Separate Part Designation	Tap isolation box
Accessory / Separate Part Destination	RS485 serial link
Product Specific Application	Lines prepolarised (2 R 620 Ohm) RS485 line isolation Line end adaptor (RC 120 Ohm, 1 nF)

Complementary

Range Compatibility	Twido programmable controller Modicon M238 logic controller
[Us] Rated Supply Voltage	24 V
Supply Circuit Type	DC
Supply	External
Electrical Connection	1 screw terminal block 2 connectors RJ45 (for tap-off)
Mounting Support	35 mm symmetrical DIN rail
Net Weight	0.1 kg

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	6.6 cm
Package 1 Width	6.5 cm
Package 1 Length	12.0 cm
Package 1 Weight	156.0 g
Unit Type Of Package 2	S02
Number Of Units In Package 2	24
Package 2 Height	15 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	4.191 kg

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Unit Type Of Package 3	P12
Number Of Units In Package 3	768
Package 3 Height	75 cm
Package 3 Width	120 cm
Package 3 Length	80 cm
Package 3 Weight	150 kg

Contractual warranty

Warranty	18 months
----------	-----------