



module XPSAK - Emergency stop - 24 V AC DC

XPSAK311144

! Discontinued on: 16 Jan 2024

① Discontinued

Main

IVIAIII		
Range Of Product	Preventa Safety automation	
Product Or Component Type	Preventa safety module	
Safety Module Name	XPSAK	
Safety Module Application	For emergency stop, switch, sensing mat/edges or safety light curtain monitoring	
Function Of Module	Proximity sensor monitoring	
	Emergency stop monitoring 1-channel wiring	
	Monitoring of electro-sensitive protection equipment (ESPE)	
	Multiple emergency stop monitoring 2-channel wiring	
	Monitoring of a movable guard	
	Sensing mat and edges monitoring	
	Emergency stop with 2 NC contacts monitoring 2-channel wiring	
	Monitoring of a movable guard associated with 2 switches and automatic start	
Safety Level	Can reach PL e/category 4 conforming to EN/ISO 13849-1	
	Can reach SILCL 3 conforming to EN/IEC 62061	
Safety Reliability Data	DC > 99 % conforming to EN/ISO 13849-1	
	MTTFd = 154.5 years conforming to EN/ISO 13849-1	
	PFHd = 7.39E-9 1/h conforming to EN/IEC 62061	
Type Of Start	Configurable	
Connections - Terminals	Captive screw clamp terminals, 1 x 0.141 x 2.5 mm² flexible with cable end, with double bezel	
	Captive screw clamp terminals, 1 x 0.141 x 2.5 mm² solid with cable end, with double bezel	
	Captive screw clamp terminals, 1 x 0.251 x 1.5 mm² flexible with cable end, with double bezel	
	Captive screw clamp terminals, 1 x 0.251 x 2.5 mm² flexible with cable end, with double bezel	
	Captive screw clamp terminals, 2 x 0.142 x 0.75 mm² flexible with cable end, with double bezel	
	Captive screw clamp terminals, 2 x 0.142 x 0.75 mm² solid with cable end, with	
	double bezel	
	Captive screw clamp terminals, 2 x 0.252 x 1 mm² flexible with cable end, with	
	double bezel	
	O-attraction and the state of the control of the co	
	Captive screw clamp terminals, $2 \times 0.52 \times 1.5 \text{ mm}^2$ flexible with cable end, with double bezel	
Output Type		
Output Type Number Of Additional Circuits	double bezel	
	double bezel Relay instantaneous opening, 3 NO circuit(s), volt-free	

Complementary

Synchronisation Time Between Inputs	Unlimited (manual start) 2 or 4 s depending of wiring (automatic start)
Supply Frequency	50/60 Hz

Maximum Power Consumption In Va	5 VA AC	
Input Protection Type	Internal, electronic	
[Uc] Control Circuit Voltage	24 V DC	
Maximum Line Resistance	28 Ohm	
Breaking Capacity	180 VA holding AC-15 C300 relay output 1800 VA inrush AC-15 C300 relay output	
Breaking Capacity 1.5 A at 24 V (DC-13) time constant: 50 ms for relay output		
Output Thermal Current 6 A per relay for relay output		
[Ith] Conventional Free Air Thermal Current	18 A	
Associated Fuse Rating	4 A gG or gL for relay output conforming to EN/IEC 60947-5-1, DIN VDE 0660 part 200 6 A fast blow for relay output conforming to EN/IEC 60947-5-1, DIN VDE 0660 part 200	
Minimum Output Current	10 mA for relay output	
Minimum Output Voltage	17 V for relay output	
Maximum Response Time On Input Open	40 ms	
[Ui] Rated Insulation Voltage	300 V (pollution degree 2) conforming to IEC 60947-5-1 300 V (pollution degree 2) conforming to DIN VDE 0110 part 1	
[Uimp] Rated Impulse Withstand Voltage	4 kV overvoltage category III conforming to IEC 60947-5-1 4 kV overvoltage category III conforming to DIN VDE 0110 part 1	
Local Signalling	4 LEDs	
Current Consumption	30 mA at 24 V AC on power supply	
Mounting Support	35 mm symmetrical DIN rail	
Net Weight	0.3 kg	
Environment		
Standards	EN/ISO 13850 EN 1088/ISO 14119	

Standards	EN/ISO 13850 EN 1088/ISO 14119 EN/IEC 60947-5-1 EN/IEC 60204-1
Product Certifications	CSA UL TÜV
Ip Degree Of Protection	IP20 (terminals) conforming to EN/IEC 60529 IP40 (enclosure) conforming to EN/IEC 60529
Ambient Air Temperature For Operation	-1055 °C
Ambient Air Temperature For Storage	-2585 °C

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	6.5 cm
Package 1 Width	12.5 cm
Package 1 Length	10.5 cm
Package 1 Weight	355.0 g
Unit Type Of Package 2	S02

Number Of Units In Package 2	12
Package 2 Height	15.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	4.786 kg

Contractual warranty

Warranty 18 months

Sustainability Green Premium*

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

	Mercury Free	
②	Rohs Exemption Information	Yes
	Pvc Free	

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information

Product datasheet

XPSAK311144

Dimensions Drawings

Dimensions

