Product datasheet





module XPSVN - zero speed detection - 230 V AC for motor power supply <= 60 Hz

XPSVNE3742P

Discontinued on: 16 Jan 2024

① Discontinued

Main

Range Of Product	Preventa Safety automation
Product Or Component Type	Preventa safety module
Safety Module Name	XPSVNE
Safety Module Application	For zero speed detection
Function Of Module	Monitoring star-delta motor starter and guard switch type XCS E Monitoring 3-phase motor + variable speed drive Monitoring XPS AK Monitoring dc motor Monitoring 3-phase motor with variable number of poles and star-delta starting Monitoring 3-phase motor Monitoring 3-phase motor with star-delta starting
Safety Level	Can reach PL d/category 3 conforming to EN/ISO 13849-1 Can reach SILCL 2 conforming to EN/IEC 62061
Safety Reliability Data	MTTFd = 124.1 years conforming to EN/ISO 13849-1 DC > 99 % conforming to EN/ISO 13849-1 PFHd = 9.26E-9 1/h conforming to EN/IEC 62061
Product Certifications	TÜV UL CSA
[Us] Rated Supply Voltage	230 V AC - 1510 %
Output Type	Relay, 1 NO + 1 NC circuit(s), volt-free
Number Of Additional Circuits	2 solid state outputs

Complementary

Product Destination	For motor power supply <= 60 Hz
Power Consumption In Va	7 VA
Input Voltage	500 Vrms
Input Detection Threshold	0.010.1 V
Breaking Capacity	180 VA holding AC-15 C300 relay output 1800 VA inrush AC-15 C300 relay output
Breaking Capacity	1.2 A at 24 V (DC-13) time constant: 50 ms for NC relay output circuit 1.5 A at 24 V (DC-13) time constant: 50 ms for NO relay output circuit 10 mA at 48 V for solid state output circuit 20 mA at 24 V for solid state output circuit
[Ith] Conventional Free Air Thermal Current	2.5 A for relay output
Associated Fuse Rating	4 A gG for relay output conforming to EN/IEC 60947-5-1, DIN VDE 0660 part 200
Standards	EN/IEC 60947-5-1 EN/IEC 60204-1

Minimum Output Current	10 mA for relay output
Minimum Output Voltage	17 V for relay output
[Ui] Rated Insulation Voltage	300 V (pollution degree 2) conforming to IEC 60947-5-1 300 V (pollution degree 2) conforming to DIN VDE 0110 parts 1 and 2
[Uimp] Rated Impulse Withstand Voltage	4 kV overvoltage category III conforming to IEC 60947-5-1 4 kV overvoltage category III conforming to DIN VDE 0110 parts 1 and 2
Local Signalling	4 LEDs
Connections - Terminals	Captive screw clamp terminals, removable terminal block flexible cable: 0.21.5 mm² without cable end, 2 wires
	Captive screw clamp terminals, removable terminal block flexible cable: 0.22.5 mm ² without cable end, 1 wire
	Captive screw clamp terminals, removable terminal block flexible cable: 0.251 mm ² with cable end, without bezel, 2 wires
	Captive screw clamp terminals, removable terminal block flexible cable: 0.252.5 mm² with cable end, with bezel, 1 wire
	Captive screw clamp terminals, removable terminal block flexible cable: 0.252.5
	mm² with cable end, without bezel, 1 wire Captive screw clamp terminals, removable terminal block flexible cable: 0.51.5 mm² with cable end, with double bezel, 2 wires
	Captive screw clamp terminals, removable terminal block solid cable: 0.21 mm² without cable end, 2 wires
	Captive screw clamp terminals, removable terminal block solid cable: $0.22.5 \ \text{mm}^2$ without cable end, 1 wire
Mounting Support	35 mm symmetrical DIN rail
Depth	114 mm
Height	99 mm
Width	45 mm
Net Weight	0.6 kg
Environment	
	ID00 (

Ip Degree Of Protection	IP20 (terminals) conforming to EN/IEC 60529 IP40 (enclosure) conforming to EN/IEC 60529
Ambient Air Temperature For Operation	-1055 °C
Ambient Air Temperature For	-2585 °C

Packing Units

r adming dimes	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	6.5 cm
Package 1 Width	12.5 cm
Package 1 Length	10.5 cm
Package 1 Weight	385.0 g
Unit Type Of Package 2	S02
Number Of Units In Package 2	12
Package 2 Height	15 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	5.082 kg
Unit Type Of Package 3	P06
Number Of Units In Package 3	192

Dealesse 2 Height	405	
Package 3 Height	105 cm	
Package 3 Width	60 cm	
Package 3 Length	80 cm	
	33 611	
Package 3 Weight	81.844 ka	

Contractual warranty

Warranty 18 months

Sustainability Green Premium*

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

	Mercury Free	
②	Rohs Exemption Information	Yes
	Pvc Free	

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information