Product datasheet

Specifications





Double contact block, Harmony XB4, silver alloy, screw clamp terminal, 1NO+1NC

ZBE205

Main

| Range Of Product | Harmony XB4 Harmony XB5 |
|-------------------------------|---|
| Product Or Component Type | Contact block |
| Device Short Name | ZBE |
| Sale Per Indivisible Quantity | 5 |
| Ip Degree Of Protection | IP20 conforming to IEC 60529 |
| Contact Operation | Slow-break |
| Contact Block Type | Double |
| Contacts Usage | Standard contacts |
| Connections - Terminals | Screw clamp terminals, <= 2 x 1.5 mm ² with cable end conforming to IEC 60947-1 Screw clamp terminals, >= 1 x 0.22 mm ² without cable end conforming to IEC 60947-1 |

Complementary

| Net Weight | 0.02 kg |
|--|--|
| Contacts Type And Composition | 1 NO + 1 NC |
| Positive Opening | With conforming to IEC 60947-5-1 appendix K |
| Operating Travel | 1.5 mm (NC changing electrical state)2.6 mm (NO changing electrical state)4.3 mm (total travel) |
| Operating Force | 4.6 N NC + NO changing electrical state |
| Mechanical Durability | 10000000 cycles |
| Tightening Torque | 0.81.2 N.m conforming to IEC 60947-1 |
| Shape Of Screw Head | Cross compatible with pozidriv No 1 screwdriver Slotted compatible with flat $Ø$ 4 mm screwdriver Slotted compatible with flat $Ø$ 5.5 mm screwdriver |
| Contacts Material | Silver alloy (Ag/Ni) |
| Short-Circuit Protection | 10 A cartridge fuse type gG conforming to IEC 60947-5-1 |
| [Ith] Conventional Free Air Thermal Current | 10 A conforming to IEC 60947-5-1 |
| [Ui] Rated Insulation Voltage | 600 V (pollution degree 3) conforming to IEC 60947-1 |
| [Uimp] Rated Impulse Withstand Voltage | 6 kV conforming to IEC 60947-1 |
| [le] Rated Operational Current | 3 A at 240 V, AC-15, A600 conforming to IEC 60947-5-1 6 A at 120 V, AC-15, A600 conforming to IEC 60947-5-1 0.1 A at 600 V, DC-13, Q600 conforming to IEC 60947-5-1 0.27 A at 250 V, DC-13, Q600 conforming to IEC 60947-5-1 0.55 A at 125 V, DC-13, Q600 conforming to IEC 60947-5-1 1.2 A at 600 V, AC-15, A600 conforming to IEC 60947-5-1 |

| Electrical Durability | 1000000 cycles, AC-15, 1 A at 230 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 1000000 cycles, AC-15, 1.5 A at 120 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 1000000 cycles, AC-15, 3 A at 24 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 1000000 cycles, DC-13, 0.15 A at 110 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 1000000 cycles, DC-13, 0.15 A at 110 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 1000000 cycles, DC-13, 0.4 A at 24 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to IEC 60947-5-1 appendix C |
|-----------------------------|--|
| Mounting Of Block | Front mounting |
| Electrical Composition Code | C2 (quantity <= 3) C4 (quantity <= 2) C6 (quantity <= 2) C10 (quantity <= 1) C10 (quantity <= 2) C13 (quantity <= 3) M2 (quantity <= 2) M4 (quantity <= 2) M8 (quantity <= 2) |
| Device Presentation | Basic element |

Environment

| Protective Treatment | тн |
|--|--|
| Ambient Air Temperature For Storage | -4070 °C |
| Ambient Air Temperature For Operation | -4070 °C |
| Standards | IEC 60947-5-1 CSA C22.2 No 14 JIS C8201-5-1 IEC 60947-5-4 IEC 60947-1 UL 508 JIS C8201-1 |
| Product Certifications | DNV CSA LROS (Lloyds register of shipping) BV GL GOST UL CCC |
| Vibration Resistance | 5 gn (f= 2500 Hz) conforming to IEC 60068-2-6 |
| Shock Resistance | 30 gn (duration = 18 ms) for half sine wave acceleration conforming to IEC 60068-2-27 50 gn (duration = 11 ms) for half sine wave acceleration conforming to IEC 60068-2-27 |

Packing Units

| Unit Type Of Package 1 | PCE |
|------------------------------|--------|
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 4.4 cm |
| Package 1 Width | 5.4 cm |
| Package 1 Length | 5.7 cm |
| Package 1 Weight | 17 g |
| Unit Type Of Package 2 | BB1 |
| Number Of Units In Package 2 | 5 |
| Package 2 Height | 5.7 cm |

| Package 2 Width | 4.4 cm |
|------------------------------|----------|
| Package 2 Length | 5.4 cm |
| Package 2 Weight | 92 g |
| Unit Type Of Package 3 | \$02 |
| Number Of Units In Package 3 | 400 |
| Package 3 Height | 15 cm |
| Package 3 Width | 30 cm |
| Package 3 Length | 40 cm |
| Package 3 Weight | 7.712 kg |

Contractual warranty

Warranty

18 months

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc
Toxic Heavy Metal Free
Mercury Free
Rohs Exemption Information Yes

Certifications & Standards

| Reach Regulation | REACh Declaration |
|--------------------------|---|
| Eu Rohs Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| China Rohs Regulation | China RoHS declaration |
| Environmental Disclosure | Product Environmental Profile |
| Weee | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Circularity Profile | End of Life Information |