



Acti9 iID - RCCB - 2P - 100A - 30mA - type AC

Local distributor code: 396893277

SEA9R11291

! Discontinued on: 15 Feb 2024

! To be end-of-service on: 15 Feb 2025

! Discontinued

EAN Code: 5018934967004

Main

Range	Acti9	
Product Name	Acti9 iID	
Product Or Component Type	Residual current circuit breaker (RCCB)	
Device Short Name	ilD	
Poles Description	2P	
Neutral Position	Left	
[In] Rated Current	100 A	
Network Type	AC	
Earth-Leakage Sensitivity	30 mA	
Earth-Leakage Protection Time Delay	Instantaneous	
Earth-Leakage Protection Class	Type AC	

Complementary

Device Location In System Outgoer Network Frequency 50/60 Hz [Ue] Rated Operational Voltage 220240 V AC 50/60 Hz Residual Current Tripping Technology Voltage independent Rated Breaking And Making Capacity Idm 1500 A Im 1500 A Im 1500 A Rated Conditional Short-Circuit Current 10 kA [Ui] Rated Insulation Voltage 500 V AC 50/60 Hz [Uimp] Rated Impulse Withstand Voltage 6 kV Contact Position Indicator Yes Control Type Toggle Local Signalling Trip indicator Mounting Mode Clip-on Mounting Support DIN rail 9 Mm Pitches 4 Height 91 mm		
[Ue] Rated Operational Voltage 220240 V AC 50/60 Hz Residual Current Tripping Technology Rated Breaking And Making Idm 1500 A Im 1500 A Rated Conditional Short-Circuit 200 A Im 1500 A Rated Conditional Short-Circuit 200 V AC 50/60 Hz [Uij] Rated Insulation Voltage 500 V AC 50/60 Hz [Uimp] Rated Impulse Withstand Voltage Contact Position Indicator Yes Control Type Toggle Local Signalling Trip indicator Mounting Mode Clip-on Mounting Support DIN rail 9 Mm Pitches 4	Device Location In System	Outgoer
Residual Current Tripping Technology Rated Breaking And Making Capacity Rated Conditional Short-Circuit Current [Ui] Rated Insulation Voltage 500 V AC 50/60 Hz [Uimp] Rated Impulse Withstand Voltage Contact Position Indicator Yes Control Type Toggle Local Signalling Trip indicator Mounting Mode Clip-on Mounting Support DIN rail 9 Mm Pitches A Idm 1500 A Im 1500 A	Network Frequency	50/60 Hz
Technology Rated Breaking And Making Capacity Rated Conditional Short-Circuit Current [Ui] Rated Insulation Voltage Soo V AC 50/60 Hz [Uimp] Rated Impulse Withstand Voltage Contact Position Indicator Yes Control Type Toggle Local Signalling Trip indicator Mounting Mode Clip-on Mounting Support DIN rail 9 Mm Pitches I dm 1500 A Im 1500 A I	[Ue] Rated Operational Voltage	220240 V AC 50/60 Hz
Capacity Im 1500 A Rated Conditional Short-Circuit 10 kA Current [Ui] Rated Insulation Voltage 500 V AC 50/60 Hz [Uimp] Rated Impulse Withstand Voltage Contact Position Indicator Yes Control Type Toggle Local Signalling Trip indicator Mounting Mode Clip-on Mounting Support DIN rail 9 Mm Pitches 4		Voltage independent
Current [Ui] Rated Insulation Voltage 500 V AC 50/60 Hz [Uimp] Rated Impulse Withstand 6 kV Voltage Contact Position Indicator Yes Control Type Toggle Local Signalling Trip indicator Mounting Mode Clip-on Mounting Support DIN rail 9 Mm Pitches 4		
[Uimp] Rated Impulse Withstand 6 kV Voltage Contact Position Indicator Yes Control Type Toggle Local Signalling Trip indicator Mounting Mode Clip-on Mounting Support DIN rail 9 Mm Pitches 4		10 kA
Voltage Contact Position Indicator Yes Control Type Toggle Local Signalling Trip indicator Mounting Mode Clip-on Mounting Support DIN rail 9 Mm Pitches 4	[Ui] Rated Insulation Voltage	500 V AC 50/60 Hz
Control Type Toggle Local Signalling Trip indicator Mounting Mode Clip-on Mounting Support DIN rail 9 Mm Pitches 4		6 kV
Local Signalling Trip indicator Mounting Mode Clip-on Mounting Support DIN rail 9 Mm Pitches 4	Contact Position Indicator	Yes
Mounting Mode Clip-on Mounting Support DIN rail 9 Mm Pitches 4	Control Type	Toggle
Mounting Support DIN rail 9 Mm Pitches 4	Local Signalling	Trip indicator
9 Mm Pitches 4	Mounting Mode	Clip-on
	Mounting Support	DIN rail
Height 91 mm	9 Mm Pitches	4
	Height	91 mm
Width 36 mm	Width	36 mm

Depth	73.5 mm	
Net Weight	0.21 kg	
Colour	White	
Mechanical Durability	20000 cycles	
Electrical Durability	AC-1: 10000 cycles	
Locking Options Description	Padlocking device	
Connections - Terminals	Single terminal top or bottom 135 mm² rigid Single terminal top or bottom 125 mm² flexible Single terminal top or bottom 125 mm² flexible with ferrule	
Wire Stripping Length	14 mm for top or bottom connection	
Tightening Torque	3.5 N.m top or bottom	

Environment

Standards	EN/IEC 61008-1	
Product Certifications	SNI	
Ip Degree Of Protection	IP20 conforming to IEC 60529 IP40 (modular enclosure) conforming to IEC 60529	
Pollution Degree	3	
Electromagnetic Compatibility	8/20 μs impulse withstand, 250 A conforming to EN/IEC 61008-1	
Ambient Air Temperature For Operation	-560 °C	
Ambient Air Temperature For Storage	-4085 °C	

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	4.0 cm
Package 1 Width	9.5 cm
Package 1 Length	10.0 cm
Package 1 Weight	230.0 g

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

	Mercury Free	
⊘	Rohs Exemption Information	Yes
②	Halogen Free Plastic Parts Product	

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations